











TECHNICAL INFORMATION / TEKNISK INFORMATION



BERGO SOFT TILE

Material:	 PE	ISO2076	FDA approved and antibacterial, 100 % environmentally friendly recyclable UV-stabilised PE-composite. PVC-free. / Livsmedelsgodkänd och antibakteriell, 100% miljövänlig återvinningsbar UV-stabiliserad polythen. Ingen PVC.
Size of tile: /Plattans storlek:		EN427	377,2 x 377,2 mm. 1 m ² / box = 7 tiles. 5 m ² / box = 35 tiles.
Thickness of tile: /Plattans tjocklek:		EN428	10,3 mm.
Weight: /Vikt:		EN430	1 tile: 0,413 kg. 1 m ² : 2,9 kg (Consumer pack). 5 m ² : 14,8 kg (Maxi-pack).
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	150 ton / 1 m ² = 1500 kg/dm ²
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance: /Halkmotstånd:		DIN51 130 SSEN-13893	R9 / V10 >0,4
Impact resistance: /Slagåtlighet:		ISO 179/1eA ASTM D746	+23 °C = NB kJ/m ² / -20 °C = NB kJ/m ² C15 kJ/m ²
Fire category /Brandklassning:		EN ISO 11925-2	E _{fl}
CE certification:		EN 14041	0402-CPD-P605080A
Determination of Antibacterial Activity	E coli	MOD JIS Z 2801:2000	≥ 99.69%
	MRSA	MOD JIS Z 2801:2000	≥ 99.67%

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
Maxi-pack	5 m ² = 35 tiles	1 pallet = 36 cartons = 180 m ²	1,20 x 0,80 x 2,41 m = 2,31 m ³ , 560 kg gross weight




By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



BergoTurfs are 100% recyclable.



The Bergo Tile - Polypropylene floor covering for use out- and indoors. Reaction to fire Class Efl. Slipperiness DS.



R9 Rutschhemmung Bewertungsgruppe
V10 Verschleißraum Bewertungsgruppe

SYSTEM
2

www.bergoflooring.com

