



BERGO ULTIMATE™

Material: Matériau :		ISO2076	Environmentally friendly recyclable UV-stabilized polypropylene. Recyceltes und umweltfreundliches UV-stabilisiertes Polypropylen. Écologique et recyclable Polypropylène stable aux UV. Miljøvenlig återvinningsbar UV-stabiliserad polypropen.
Size: Größe: Dimensions : Storlek:		EN427	1 tile / Platte / dalle / platta: 375,3 x 375,3 mm. Building dimensions / Baumaße / dimensions de construction / Byggmått: 376,7 x 376,7 mm
Thickness of tile: Stärke, eine Platte: Épaisseur de dalle : Plattans tjocklek:		EN428	12,4 mm. Thickness with underlayment Re-bounce 5 mm: 17,4 mm.
Weight: Gewicht: Poids : Vikt:		EN430	1 tile / Platte / dalle / platta: 0,500 kg. 1 m² = 7 tiles / Platten / dalles / plattor: 3,5 kg.
Point load: Pungtbelastung: Charge ponctuelle : Punktbelastning:		Qualified test by Bergo Qualifizierte test by Bergo Test confirmé par Bergo Kvalificerad test av Bergo	500 ton / tonnes / 1 m² = 5000 kg/dm²
Light fastness/Colorchange: Lichtechtheit: Résistance à la lumière : Ljusbeständighet:		EN 14836 (>3) ISO 20105-A02	4-5 4/5
Weather Fastness /UV-Florida test (1-5): Witterungsbeständigkeit/UV-Floridatest (1-5): Résistance aux intempéries /UV- Test Floride (1-5) : Väderbeständighet / UV-Floridatest (1-5)		ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance: Rutschhemmung: Propriétés antidérapantes : Halkmotstånd:		EN13036-4	Dry: 109 PTV Wet: 61 PTV
Impact resistance: Schlagfestigkeit: Résistance aux chocs : Slagtåligghet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m² / -20 °C = 5 kJ/m² C15 kJ/m²
Fire category: Brandklasse: Classe incendie : Brandklassning:		EN ISO 11925-2	E _{fl}
Shock absorption without Re-bounce underlay: Stoß-Absorption ohne Re-bounce Unterlag: Absorption des chocs sans Re-bounce: Stötupptagning utan Re-bounce underlag:	EN 14877	EN 14808	6 %
Shock absorption with Re-bounce 5 mm underlay: Stoß-Absorption mit Re-bounce 5 mm Unterlag: Absorption des chocs avec Re-bounce 5 mm: Stötupptagning med Re-bounce 5 mm underlag:	EN 14877	EN 14808	33 %
Vertical deformation: Vertikale Verformung Déformation verticale : Vertikaldemoformation:	EN 14877	EN 14809	1,3 mm
Vertical ball rebound: Ballreflexion: Comportement vertical du ballon : Bollstuds:	EN 14877	EN 12235	94 %
Resistance to wear: Verschleißfestigkeit: Résistance à l'usure : Nötningmotstånd:	EN 14877	EN ISO 5470-1	119 mg
Water infiltration rate (broken-through pattern): Wasserinfiltrationsrate (unterbrochenes Muster) Taux d'infiltration de l'eau : Vattengenomsläpplighet:	EN 14877	EN 12616	Requirement very well achieved. Anforderung sehr gut erricht. Exigences parfaitement remplies. Uppfyller kraven med god marginal.

Futsal AAA Test results

	Results	Requirements
Point Elastic::	25,2%	≥ 18-75%
Vertical Deformation:	2,7 mm	≤ 6,0 mm

Bergo Ultimate™ is tested, approved and certified by FIBA in the following criteria:

- ✓ FIBA-approved in Level 1 and 2.
- ✓ For portable installations



Bergo Ultimate™ is tested and approved according to **EN14877** and fulfils **ALL** requirements for the important European norm for outdoor sports flooring.



Bergo Ultimate™ is classified by IFT.



BREEAM® SE



Packaging
Packung
Conditionnement
Frp
Maxi-pack carton
Bulk/ Lose verpackt / Vrac

Quantity / packaging unit
Menge / Verpackungseinheit
Quantité / unité conditionnement
Kvantitet / frp
4 m² = 28 tiles / Platten / Dalles / plattor

Quantity / pallet
Menge / Palette
Quantité / palette
Antal / pall
18 cartons = 72 m²
75,5 m²

Size of pallet
Größe eine Palette
Dimensions de palette
Pallstorlek
1,20 x 0,8 x 1,26 m (lxbh) = 1,2 m³, 284 kg gross weight / Bruttogewicht / Poids brut / bruttovikt
Double stacked: height 2,52
1,20 x 0,8 x 1,25 m = 1,2 m³, 287 kg gross weight / Bruttogewicht / Poids / bruttoviktbrut



By normal use and treatment the material warranty time is 15 years.
Die Bergo-Floor- / Polypropylen-Belastung für den Innen- und Außenbereich.
Erandringningstid 15 år. Belastningstid 15 år.
Avec une utilisation et un traitement normaux, la durée de garantie matérielle est de 15 ans.
Vid normal användning och behandling är materialets garanterade 15 år.



Bergo Flooring AB fulfylls the requirements of ISO 9001.
Bergo Flooring AB erfüllt die Anforderungen der Norm ISO 9001.
Bergo Flooring AB est certifié selon la norme ISO 9001.
Bergo Flooring AB er certifisert etter la norme ISO 9001.



Bergo Floors are 100% recyclable.
Bergo Belastingen sind 100% recycelbar.
Les sol Bergo sont recyclables à 100 %.
Bergo golv er 100% återvinningsbar.

