











BERGO XL

Material: Matériau :	 ISO2076	Environmentally friendly recyclable UV-stabilized PP-composite. (PVC-free) Umweltfreundliches recycelbares UV-stabilisiertes PP-Composite. (Kein PVC). Composite PP écologique, recyclable à 100 % et résistant aux UV. (Sans)PVC. Miljövänlig, 100 % återvinningsbar UV-stabiliserad PP-komposit. (PVS-fri.)
Size: Größe: Dimensions : Storlek:	 EN427	377,2 x 377,2 mm. 1 m ² / box = 7 tiles. 5 m ² / box = 35 tiles.
Thickness of tile: Stärke, eine Platte: Épaisseur de dalle : Plattans tjocklek:	 EN428	10,1 mm.
Weight: Gewicht: Poids : Vikt:	 EN430	1 tile: 0,350 kg. 1 m ² : 2,63 kg (Consumer pack). 5 m ² : 12,85 kg (Maxi-pack).
Point load: Pungtbelastung: Charge ponctuelle : Punktbelastning:	 Qualified test by Bergo Qualifizierte test by Bergo Test confirmé par Bergo Kvalificerad test av Bergo	250 ton / 1 m ² = 2500 kg/dm ²
Light fastness: Lichtechtheit: Résistance à la lumière : Ljusbeständighet:	 EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
Weather Fastness /UV-Florida test (1-5): Witterungsbeständigkeit/UV-Floridatest (1-5): Résistance aux intempéries /UV- Test Floride (1-5) : Väderbeständighet / UV-Floridatest (1-5)	ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance/Friction: Rutschhemmung/Reibung: Propriétés antidérapantes / Friction : Halkmotstånd/Friktion:	 SSEN-13893	>0,3
Impact resistance: Schlagfestigkeit: Résistance aux chocs : Slagtålighet:	 ISO179/1eA ASTM D746	+23 °C = 20 kJ/m ² / -20 °C = 5 kJ/m ² C15 kJ/m ²
Fire category: Brandklasse: Classe incendie : Brandklassning:	 EN ISO 11925-2	E _{fl}
CE certification: CE-Zertifizierung: CE-certifiering: Certification CE :	 EN 14041	0402-CPD-P605080A

Packaging Packung Conditionnement Frp	Quantity / packaging unit Menge / Verpackungseinheit Quantité / unité conditionnement Kvantitet / frp	Quantity / pallet Menge / Palette Quantité / palette Antal / pall	Size of pallet Grösse eine Palette Dimensions de palette Pallstorlek
Consumer-pack	1 m ² = 7 tiles/Platten/Dalles/plattor	90 cartons = 90 m ²	1,20 x 0,80 x 1,23 m = 1,18 m ³ , 262 kg gross weight
Maxi-pack	5 m ² = 35 tiles/Platten/Dalles/plattor	18 cartons = 90 m ²	1,20 x 0,80 x 1,25 m = 1,2 m ³ , 250 kg gross weight




By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



SYSTEM
2



www.bergoflooring.com